

## INDOSTAB LS – 333

### INTRODUCTION:

INDOSTAB LS-333 is the first generation Lead based stabilizer system. It is available in flakes form and used for high output PVC extrusion, recommended filler loading with LS-333 should be in the range up to 20 phr.

### SPECIFICATION:

Property	Specification
Appearance	Off. White Creamy Flakes
Metal Content as PbO	Approx. 32%
Specific Gravity	1.40 to 1.60
Moisture Content	Max. 1.0%
Softening Point	90-95 °C

### APPLICATION:

- For PVC extrusion applications (Pipe, Conduit, Profile and Foam Boards).

### DOSAGE:

- Recommended dosage 2.0-3.0 Phr.

### PACKAGING:

- INDOSTAB LS-333 is available in 25 kgs bags.

DISCLAIMER: The information, illustrations and suggestions of the Company herein are based on the results of tests and experiments conducted on the products. Nothing herein should be construed as a warranty or guarantee of whatsoever nature for which the Company assumes any legal responsibility, as conditions and methods of use of the products are beyond the control of the Company. It is left to the absolute discretion and knowledge of the prospective user to determine the suitability of the products and suggestions before procuring and adopting them on commercial scale. Nothing herein is to be construed as permission, inducement or recommendation to practice any patented invention without a proper license.”